

Quelques lignes de commandes fréquemment utilisables

Copie de fichiers

- copier un fichier vers une destination (par exemple serveur web), avec droits -rw-r-r- :

```
sudo cp fichier.mpg /var/www/html
```

Gestion de permission, propriétaires,...

- Changer récursivement à partir du répertoire courant le propriétaire et le groupe :

```
chown -R username:groupeusername .
```

- Changer les permissions de tous les fichiers du répertoire :

```
chmod 644 *
```

- Supprimer les permissions de lecture et exécution aux utilisateurs “tout le monde” pour son répertoire personnel :

```
chmod -R o-rx /home/username
```

ou

```
chmod -R 750 /home/username
```

- ...

Renommer l'ordinateur

- <http://askubuntu.com/questions/314773/rename-computer-in-ubuntu-13-04> :
 - `sudo hostname your-new-name`
 - add the new hostname to your `/etc/hosts` file with “`sudo nano /etc/hosts`”. Find these lines and change the original name to your new hostname:
 - 127.0.0.1 localhost
 - 127.0.1.1 your-new-name
 - Restart the computer or all services that use the old name.

À classer

- `free -h`

- `cat /proc/meminfo`
- `vmstat -s`
- `top / htop`



- <http://www.commandlinefu.com/commands/view/7952/tar.gz-with-gpg-encryption-on-the-fly>

From:

<https://dvillers.umons.ac.be/wiki/> - **Didier Villers, UMONS - wiki**

Permanent link:

https://dvillers.umons.ac.be/wiki/floss:commandes_frequentes?rev=1482405455

Last update: **2016/12/22 12:17**

